

**Average Traffic Flow, Peak-hour Traffic Flow
and its Ratio to Daily Traffic Flow
for Government Tolled Tunnels and Tai Lam Tunnel in 2024**

Tunnel	Average Traffic Flow (in two-way vehicles)	Peak-hour Traffic Flow (in two-way vehicles) ¹	Ratio
Cross-Harbour Tunnel	94 700	31 300	0.33
Eastern Harbour Crossing	72 100	28 900	0.40
Western Harbour Crossing	102 500	39 400	0.38
Tate's Cairn Tunnel	59 800	25 900	0.43
Aberdeen Tunnel	62 700	22 100	0.35
Lion Rock Tunnel	86 700	30 400	0.35
Shing Mun Tunnels	50 400	20 000	0.40
Eagle's Nest Tunnel, Sha Tin Heights Tunnel and Tai Wai Tunnel	67 900	27 900	0.41
Tai Lam Tunnel ²	38 700	16 200	0.42

Note 1: The figures listed in the table represents the traffic flow of government-tolled tunnels and Tai Lam Tunnel from Monday to Friday (excluding public holidays) in 2024. Except for the three Road Harbour Crossings (RHCs), “peak-hour traffic flow” refers to the traffic flow from 7 a.m. to 10 a.m. and from 5 p.m. to 8 p.m. (six hours in total). To more accurately reflect cross-harbour traffic, the “peak-hour traffic flow” for the three RHCs refers to the traffic flow from 7:30 a.m. to 10:30 a.m. and from 4:30 p.m. to 7:30 p.m. (six hours in total).

Note 2: Tai Lam Tunnel was operating under the Build-Operate-Transfer mode during this period.